


TSM 500 TSM/K 500

TECSEDO® SAFE Micro



Panel Weight: ST WG POLY WG SM P25 & P5 POLY 25 P45 & P35 SAND 4.60 Kg/m 5.00 Kg/m 4.85 Kg/m Weight Tolerance ±5% Ridges (Standard) 125 mm Ridges (K Version) 100 mm 500 mm < 0.022 K Watt m °C 0.50 I (ISO 717) 25 Soundproof Index (dB) 40 mm

Panel weight is for indication purposes only. Due to the typical tolerances getted during the several steps of the panels components manufacturing process, variations in the final weight of the panel can be found. For this reason and in accordance with the industrial "Best Practices", Teosedo recommends to weigh the panels before using them for each door assembly, in order to choose the most suitable springs.



FINISHING	COATING		COLOURS*					* Printed colours are for example only. To ensure proper colour and finishing representation, please contact TECSEDO and request a sample.				
External Face	External Face	External Face	External F	ace				representati	on, piease o	contact legset	oo and requ	iest a sampie.
STUCCO												
	5μm Paintable Primer		STANDARD GREY									
	25µm Polyester	STANDARD COLOURS	RAL 8014	RAL 9002	RAL 9010							
		OTHER COLOURS	RAL 6005	RAL 6009	RAL 7016	RAL 8017	RAL 9006	RAL 9007	available on	L colours are request, subject um quantities		
WOODGRAIN												
	5µm Paintable Primer		STANDARD GREY									
	25µm Polyester	STANDARD COLOURS	RAL 8014	RAL 9002	RAL 9010							
		OTHER COLOURS	RAL 6005	RAL 6009	RAL 7016	RAL 9006	available on	L colours are request, subject um quantities				
	45 µm Super Poliester Multilayer HD+		V-GOLDEN	V-DARK	V-WENGÈ	V-MAHOGANY	V-WINCHESTE	R				
POLYGRAIN												
	25µm Polyammidic		RAL 7016	RAL 9016								
SANDGRAIN												
	35µm Super Polyester Wrinkled		RAL 7016									
SMOOTH												
-	45 µm Super Poliester Multilayer HD+		V-GOLDEN	V-DARK	V-WENGÈ	V-MAHOGANY	V-WINCHESTE	R				
INTERNAL FACE	COLOUR	RS	25µm F	Polyester	RAL 9002 Stud		90	AL 010 tucco		RAL 9002 Smooth		RAL 9010 Smooth