


**TSQ** 500 **TSQ/K** 500

## TECSEDO® SAFE Quadro





	<u></u>		
'n		Panel Weight: WG P25 & P5 WG P45 Weight Tolerance Ridges (Standard) Ridges (K Version)	4.60 Kg/m 4.85 Kg/m ±5% 125 mm 100 mm
500 mm		λ mW °C	<0.022
	,	K Watt m °C	0.50
	_4	I (ISO 717) Soundproof Index (dB)	25
`			

40 mm

Panel weight is for indication purposes only.

Due to the typical tolerances getted during the several steps of the panels components manufacturing process, variations in the final weight of the panel can be found. For this reason and in accordance with the industrial "Best Practices", Tecsedo recommends to weigh the panels before using them for each door assembly, in order to choose the most suitable springs.

External Face External Face External Face							* Printed colours are for example only. To ensure proper colour and finishing representation, please contact TECSEDO and request a sample.					
WOODGRAIN												
	5µm Paintable Primer		STANDARD GREY									
	25µm Polyester		RAL 8014	RAL 9002	RAL 9010							
	,	OTHER COLOURS	RAL 6005		RAL 7016	RAL 8017	RAL 9006	RAL 9007	available or	AL colours are request, subject um quantities		
	45 µm Super Poliester Multilayer HD+		V-GOLDEN	V-DARK	V-WENGÈ	V-MAHOGANY	V-WINCHESTER	1				
INTERNAL FACE	COLOUF	RS	25µm F	olyester	RAL 9002 Stuce		The second second	AL 110 ucco		RAL 9002 Smooth		RAL 9010 Smooth