


**TBR V16 610 & TBR/K V16 610**

**TECSEDO® BASE Rake**

**V16**

TBR V16 610  
RAL 8014 - STUCCO

TBR/K V16 610  
RAL 9010 - SMOOTH



Panel Weight:	5.60 kg/m
Weight Tolerance	±5%
Ridges (Standard)	122 mm
Ridges (K Version)	101 mm
$\lambda \frac{mW}{m^{\circ}C}$	<0.022
$K \frac{Watt}{m^{\circ}C}$	0.50
I (ISO 717)	25
Soundproof Index (dB)	25

Panel weight is for indication purposes only. Due to the typical tolerances gotten during the several steps of the panels components manufacturing process, variations in the final weight of the panel can be found. For this reason and in accordance with the industrial "Best Practices", Tecse recommends to weigh the panels before using them for each door assembly, in order to choose the most suitable springs.

FINISHING External Face	COATING External Face	TYPE External Face	COLOURS* External Face	* Printed colours are for example only. To ensure proper colour and finishing representation, please contact TECSEDO and request a sample.														
<b>STUCCO</b>																		
	5µm Paintable Primer		STANDARD GREY															
	25µm Polyester	STANDARD COLOURS	RAL 8014	RAL 9002	RAL 9010													
		OTHER COLOURS	RAL 3000	RAL 5010	RAL 6005	RAL 7016	RAL 8017	RAL 9006	RAL 9007	Other RAL colours are available on request, subject to minimum quantities								
	CORUS SCALE	MERLIN GREY	GOOSEMING GREY	ALBATROS	OCEAN BLUE	SOLENT BLUE	SARGASSO BLUE	JUNIPER GREEN	HERITAGE GREEN	OLIVE GREEN (RAL-6003)	MOORLAND GREEN	POPPY RED	AZTEC YELLOW					
<b>SMOOTH</b>																		
	25µm Polyester		RAL 7016	RAL 9002	RAL 9006	RAL 9007	RAL 9010											
<b>INTERNAL FACE</b>	<b>COLOURS</b>		25µm Polyester		RAL 9002	RAL 9010	RAL 9002	RAL 9010										
			Stucco		Stucco	Smooth	Smooth											