


**TBR V16 500 & TBR/K V16 500**
**TECSEDO® BASE Rake**
**V16**

 TBR V16 500  
RAL 1021 - STUCCO

 TBR/K V16 500  
RAL 9002- SMOOTH


Panel Weight:	4.70 kg/m
Weight Tolerance	±5%
Ridges (Standard)	125 mm
Ridges (K Version)	100 mm
$\lambda \frac{mW}{m^{\circ}C}$	<0.022
$K \frac{Watt}{m^{\circ}C}$	0.50
I (ISO 717)	25
Soundproof Index (dB)	25

Panel weight is for indication purposes only. Due to the typical tolerances gotten during the several steps of the panels components manufacturing process, variations in the final weight of the panel can be found. For this reason and in accordance with the industrial "Best Practices", Tecsedo recommends to weigh the panels before using them for each door assembly, in order to choose the most suitable springs.

FINISHING External Face	COATING External Face	TYPE External Face	COLOURS* External Face	* Printed colours are for example only. To ensure proper colour and finishing representation, please contact TECSEDO and request a sample.							
<b>STUCCO</b>											
	5µm Paintable Primer		STANDARD COLOURS	RAL 8014	RAL 9002	RAL 9010					
	25µm Polyester	STANDARD COLOURS	RAL 1021	RAL 3000	RAL 5010	RAL 6005	RAL 6009	RAL 7016	RAL 8017	RAL 9006	RAL 9007
OTHER COLOURS											
<b>SMOOTH</b>											
	25µm Polyester		RAL 7016	RAL 9002	RAL 9006	RAL 9007	RAL 9010				
<b>INTERNAL FACE</b>	<b>COLOURS</b>	25µm Polyester	RAL 9002 Stucco	RAL 9010 Stucco	RAL 9002 Smooth	RAL 9010 Smooth					